MAKE CHAMPION


MODEL 710 / 720 & 730 A / A.W.D.ENGINE CUMMINS

44

File Section 3 Lube Folio

Code No:

87-3-05



STEERING CYLINDER 4 PTS. 44

DRAWBAR BALL STUD 1 PT.


CIRCLE TURN CYL. & CIRCLE CRANK 4 PTS.

TILT CYLINDER 4 PTS. 44

HIGH LIFT CYL BALL CAP 2 PTS. 44

SIDE SHIFT LINK 2 PTS. 44 ARTICULATIONCYL. 4PTS.

Circle Top Face, Clamp Plate And Guide Plate Bearing Surfaces, Side Shift Bar And Side Shift Rails, Are To Be Washed And Lubricated With A Light Coat Of Graphite Spray (13M1467) & Clean Surfaces As Often As Conditions Dictate.



40 HOUR SERVICE

LUBRICATION **PRODUCTS**

44 PIVOT BLOCK 2 PTS.

CIRCLETURN VALVE 1 PT.

44 HIGHLIFT MOUNTING LUGS 4 PTS.

44 LATCH PIN 2 PTS.

44 HIGH LIFT ARM 4 PTS.

36**B** GL Gear Lube

85W 140

FCO

Fleet

rankcase

Oil

30 ATF

Auto Trans.

TANDEM SLEEVE THRUST PLATE 2 PTS.

> 44 MPG Multiple Purpose Grease#2

PUMP GEARBOX DRIVE SHAFT 3 PTS.

CHECK EACH SHIFT

CHECK FLUID LEVELS IN THE FOLLOWING:

Radiator (cold) Engine [1] Transmission [1] Hydraulic Tank [1] Fuel Tank [1]

WARNING: See 94-10-09 and operators manual

PRODUCT #

30

-	_1	F		L	T	E	F	?	S	
_	Т		_		_					_

SE	ER'	<u>VIC</u>	E	IN.	TE	<u>RV</u>	AL	<u>S</u>
160	Но	ur S	erv	ice				T

Change Engine Oil And Filter	18
Change Engine Oil And Filter	HBF
Lube Upper And Lower Driveshaft	44
Check Transmission	30
Check Tandem Case Check Final Drive	30
Check Final Drive	36B
Check Planetary Unit Front Wheels	36B
Check Pump Drive Gear Box	36B

Sample Hydraulic Fluid (NOTE #4)..... **480 HOUR**

Note #1 & #4

Note #3

Change Fuel Filters Clean Transmission Suction Screen

960 HOUR

Note #3

Change Transmission Oil And Filter			
Change Hydraulic Filter	30		
Change Hydraulic Filter	36B		
Change Final Drive Oil	36B		
Change Pump Drive Gear Box Oil			
Change Tandem Case Oil	30		

Change Tandem Case Oil

APPLICATION	EDP#	MFG.	MFG.#
Air Primary	39 M 2019	FRAM	CA 6324
Air Secondary	39 M 2020	FRAM	CA 3989
Oil (Full Flow)	39 M 2171	FRAM	PH 3976
Oil (Bypass)	39 M 1971	FRAM	PH 3757
Fuel Primary	39 M 1528	FRAM	P 3401
Fuel Secondary	39 M 2128	FRAM	P 4102
Coolant	39 M 2168	FRAM	PR 3383
Transmission	39 m 2156	Donaldson	P 16-5705
Hydraulic	39 m 2212	FRAM	P 6885
		1	

Note #1

Service intervals may be altered by Equipment Shop Superintendent during unusual operating conditions. Note #2

If vehicle is equipped with air restriction indicator: Change primary element when restriction gauge reads in the red zone. Change secondary element every third primary change.

If vehicle has no air restriction indicator: Fonow manufacturer's recommended service instructions. Note #3

Each service interval progression includes all previous service interval operations.

Note #4

Send representative sample of fluid (from main stream of system at operating temperature) to current analysis contract lab (See 96-10-01). Take all corrective actions as suggested by analysis results.